


Customer Care and Maintenance Instructions for Nan Ya Doors



To prolong the life of the door surface finish, it is recommended that the GRP composite door is cleaned regularly. This should be completed at least once per month but will depend upon the doors location and exposure to contaminants such as dirt and salt etc.

- Do;**
- It is recommended that the door is cleaned with specially formulated door wipes which are available from Distinction Door Solutions. Alternatively, the door surface can be washed with warm soapy water (*washing up liquid is suitable*) and wipe dry with a soft cloth.
 - When the door is closed always ensure top and bottom locking points are engaged to assist in the reduction of thermal movement.



To sustain the gloss finish, apply 2 to 3 coats of König Maintenance Lacquer every 6 to 12 months.

Do Not;

- Use aggressive cleaning methods, abrasive cleaners or scouring pads on the surface of the door.
- Use high pressure of steam cleaners.
- Use any type of bleach, solvent (*eg white spirit, methylated spirit, cellulose thinners or acetone/nail varnish remover*).
- Use of adhesives of any type or tack for providing temporary protection.
- Use of adhesives of any type or tack for the temporary fixing of seasonal or other decorations etc.
- Use excessive length key chains, please try and avoid contact with these and any other sharp objects you may be carrying.



A repair system is available to deal with accidental damage such as dents or scratches. For details please contact Distinction Door Solutions.

NOTICE TO ALL INSTALLERS OF GRP COMPOSITE DOORS

Please Note; it is recommended that installers pass this information to their customers. This is to ensure that they do not invalidate the warranty by the use of abrasive cleaners, prohibited chemicals or temporary adhesives on the surface of the door.