

**ORDER GUIDELINES**

**MAXIMUM AND MINIMUM DOOR SIZES**

STYLE	DOOR WIDTHS		DOOR HEIGHTS			
	MINIMUM	MAXIMUM	MINIMUM		MAXIMUM	
			FRAME / INTEG	PART M LT	FRAME / INTEG	PART M LT
220	1500	2126	2020	2000	2400	2400
330	1800	3138	2020	2000	2400	2400
321	1800	3138	2020	2000	2400	2400
440	3000	4150	2020	2000	2400	2400
431	2350	4150	2020	2000	2400	2400
422	3000	4150	2020	2000	2400	2400
550	2925	5162	2020	2000	2400	2400
541	2925	5162	2020	2000	2400	2400
532	2925	5162	2020	2000	2400	2400
660	4500	6000	2020	2000	2400	2400
651	3475	6000	2020	2000	2400	2400
642	4500	6000	2020	2000	2400	2400
633	3475	6000	2020	2000	2400	2400
770	4050	6000	2020	2000	2400	2400
761	4050	6000	2020	2000	2400	2400
752	4050	6000	2020	2000	2400	2400
743	4050	6000	2020	2000	2400	2400

*NB: Heights noted do not include additional thermally broken sill.  
 Allow 26.5mm for this if it is required.*