

BI-FOLDING DOOR ORDER FORM

Company: _____
 Address: _____

 Postcode: _____
 Tel: _____
 Fax: _____
 Contact Name: _____
 Email: _____

Requested Delivery Date: _____ Pages
 Order Reference: _____ of
 Signature: _____

FOLDING OPTIONS (Viewed from outside)

NB. Minimum sash width 550mm per pane, maximum sash width 1000mm per pane

Total number of leaves For Example: 3 Total number of door leaves	Number of leaves folding left 1 Number of door leaves opening left	Number of leaves folding right 2 Number of door leaves opening right
--	---	---





DIMENSIONS

Overall width: _____

Maximum width: 6000mm
Overall height: _____

Maximum height: 2400mm

EXTERNAL STYLING

Standard Pencil Round 
Additional lead time and cost
 Chamfered 
 Squared 
 Decorative 
44mm Triple Glazed - Pencil Round only

FRAME COLOUR

Standard lead time

EXTERNAL	INTERNAL
<input type="checkbox"/> White	<input type="checkbox"/> White
<input type="checkbox"/> Grey 7016	<input type="checkbox"/> Grey 7016

Extended lead time

<input type="checkbox"/> Black 9005	<input type="checkbox"/> Black 9005
<input type="checkbox"/> Brown 8017	<input type="checkbox"/> Brown 8017
<input type="checkbox"/> Chartwell Green 6019	<input type="checkbox"/> Chartwell Green 6019
<input type="checkbox"/> Light Grey 7001	<input type="checkbox"/> Light Grey 7001

RAL _____ RAL _____

OPENING IN/OUT

Open in Open out

CILL TYPE

Inward/Outward Opening

Frame - No cill
 Frame - 150mm cill

Outward Opening only

Part M low threshold
 Part M low threshold ramp/cover*
 Part M low threshold ramp/ramp*
**All Silver Anodised Aluminium*

TRICKLE VENTS

YES NO
Please indicate positions below


HARDWARE OPTIONS

Satin Silver
 Matt Black
 Brushed Graphite

*Locks/keeps are Anodised Silver
 Roller units are Black Anodised powder finish
 Brushed Graphite uses Anodised Black hinges
 Hinges are Black unless otherwise stated*

GLAZING OPTIONS

Unglazed (All Toughened)
 Standard double glazed - 28mm (1.5 W/m²K U-value*)
 Triple glazed - 44mm (1.0 W/m²K U-value*)

Elite double glazed - 28mm (1.4 W/m²K U-value*)
Add Secured by Design Upgrade
  Standard double glazed (Laminated) - 28mm (1.5 W/m²K U-value*)

**Figures quoted are whole door U-values based on BFRC standard bi-fold door*

GLAZING BEADS

Squared/Squared - 28mm - 4 Sides
 Squared/Squared - 44mm - 4 Sides

ADD ON

25mm Add On

Left
 Right
 Top

SKETCH YOUR DIAGRAM HERE: (Viewed from outside)

Additional notes: _____
